DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS

REGISTERED CIVIL ENGINEER DATE

PLANS APPROVAL DATE

REGISTERED PROFESSIONAL ENGINEER No. Exp. CIVIL STATE OF CALIFORNIA

The State of California or its officers or agents shall not be responsible for the accuracy or completeness of scanned copies of this plan sheet.

The Registered Civil Engineer for the project is responsible for the selection and proper application of the component design and any modifications shown.

TABLE OF REINFORCING STEEL DIMENSIONS AND DATA

DESIGN H	6′	8′	10′	12′	14′	16′	18′	20′	22′	24′
W	9′-0″	9′-0″	9′-6″	10′-3″	11′-3″	12′-9″	14′-0″	15′-9″	17′-3″	18′-9″
F SPREAD FOOTING	1′-3″	1′-3″	1′-3″	1′-3″	1′-6″	1′-9″	1′-9″	2′-3″	2′-6″	2′-6″
BATTER	0	½:12	½:12	½:12	½:12	½:12	⅝:12	⅝:12	⅝:12	¾:12
ⓐBARS						#7 @ 15	#7 @ 12	#7 @ 12	#8 @ 12	#6 @ 6
ⓑBARS	#8 @ 12	#8 @ 12	#7 @ 6	#7 @ 6	#7 @ 6	#9 @ 7.5	#9 @ 6	#10 @ 6	#10 @ 6	#8 @ 6 ℄
ha			5′-0″	6′-0″	7′-0″	7′-0″	6′-0″	7′-0″	6′-9″	7′-6″
hb						11′-6″	12′-0″	13′-3″	16′-0″	15′-6″
ⓒBARS	#7 @ 12	#8 @ 12	#7 @ 6	#9 @ 6	#9 @ 6	#11@ 7.5	#8 @ 6 ℄	#9 @ 6 ℄	#9 @ 6 ℄	#10 @ 6 ℄
hz			3′-6″	4′-0″	4′-9″	7′-0″	5′-9″	6′-9″	7′-6″	9′-0″
SER I: B′(ft), q_0'(ksf)	7.5, 1.5	7.1, 1.9	7.2, 2.2	7.6, 2.5	8.3, 2.8	9.6, 3.0	10.6, 3.3	12.1, 3.6	13.3, 3.9	14.6, 4.1
STR, Ia: B′(ft), q_0(ksf)	7.9, 2.9	7.4, 3.3	7.4, 3.7	7.8, 4.1	8.3, 4.5	9.5, 4.8	10.5, 5.0	11.9, 5.6	13.1, 6.0	14.3, 6.4
STR, Ib: B′(ft), q_0(ksf)	6.0, 2.0	5.5, 2.5	5.6, 2.9	5.9, 3.3	6.4, 3.7	7.6, 3.9	8.7, 4.1	9.9, 4.5	11.0, 4.9	12.1, 5.2
STR, IIIa: B′(ft), q_0(ksf)	6.0, 2.7	6.0, 3.0	6.4, 3.4	7.0, 3.7	7.8, 4.1	9.1, 4.4	10.2, 4.6	11.7, 5.1	12.9, 5.4	14.2, 5.7
STR, IIIb: B′(ft), q_0(ksf)	5.3, 2.5	5.2, 2.8	5.5, 3.1	6.0, 3.3	6.7, 3.7	8.0, 3.9	8.9, 4.0	10.4, 4.4	11.5, 4.7	12.7, 5.0
STR, Va: B′(ft), q_0(ksf)	7.5, 2.8	7.1, 3.2	7.2, 3.5	7.6, 3.9	8.2, 4.3	9.4, 4.6	10.4, 4.9	11.8, 5.3	13.0, 5.8	14.3, 6.1
STR, Vb: B′(ft), q_0(ksf)	5.7, 2.2	5.3, 2.6	5.4, 3.0	5.8, 3.4	6.4, 3.8	7.7, 3.9	8.7, 4.0	10.0, 4.5	11.1, 4.9	12.2, 5.1
Ext I: B′(ft), q_0(ksf)	4.0, 3.4	3.0, 4.7	2.5, 6.5	2.1, 9.2	1.8, 13.3	2.1, 14.4	2.3, 16.9	2.6, 17.2	2.9, 18.4	3.3, 19.3

LEGEND:

SER: service limit state
STR: strength limit state
EXT: extreme event limit state
B′: effective footing width (ft)
q_0': net bearing stress (ksf)
q_0: gross uniform bearing stress (ksf)

℄ : 2 bar bundle

BRIDGE STANDARD DETAILS

xs14-340-2	July 2014	The components of the Bridge Standard Details have been prepared under the responsible charge of the Technical Owner, a registered civil engineer in the State of California
FILE NO.	APPROVAL DATE	

Refer to: http://www.dot.ca.gov/hq/esc/techpubs/manual/bridgemanuals/bridge-standard-detail-sheets/index.html

FILE => xs14-340-2.dgn
USERNAME => s136236 TIME PLOTTED => 10:45 DATE PLOTTED => 18-JUL-2016

ORIGINAL SCALE IN INCHES FOR REDUCED PLANS 0 1 2 3

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

DIVISION OF ENGINEERING SERVICES

BRIDGE NO.
POST MILE

RETAINING WALL TYPE 5SW-DETAILS NO. 2

UNIT:
PROJECT NUMBER & PHASE:
CONTRACT NO.:

DISREGARD PRINTS BEARING EARLIER REVISION DATES

REVISION DATES				SHEET	OF
6-19-14	7-14-16				